RoHS Compliant







SPECIFICATION

1 Contact resistance: ≤20mΩ
2 Insulation resistance: ≥100MΩ
3 Rated voltage: 150 V AC DC
4 Rated current: 1.5 A AC DC
5 Withstand Voltage: 1000V AC/minute
6 Temperature Range:-25℃～+85℃

ORDER INFORMATION:

B1503M-03-F2MC-R-F(1μ″)

- PART No.
- No.OF CIRCUITS: 03
- PLASTIC MATERIAL: F2M=LCP(Nature)
- PACKAGING: R=Reel
- PLATING: C=Ni+Selective gold plated



SUGGESTED PCB LAYOUT
(COMPONENT SIDE)

B1 注：3枚Pin针分两次装配（Pin1.3和Pin2），
因此有一定的落差，落差不超过0.15mm。

专利产品

REV.	DATE	DESCRIPTION	APPD.	NO.	DESCRIPTION	QTY	MATERIAL	PLATING/COLOR
C/0	2022.08.10	统一标准，更新模板	王程伟	③	Solder Tab	2	Brass	Matte Sn
B/1	2021.08.14	增加落差说明	黄羡程	②	Contacts	3	Phosphor Bronze	Ni+Selective gold plated 1μ″
B/0	2021.03.12	NEW RELEASE		①	Insulator	1	LCP(UL94V-0)	Nature

Tolerance
X.X ±0.30
X.XX ±0.20
X.XXX ±0.10
Angle ±3.0°

UNIT: mm

CNJST 捷仕泰企业

Model No.:B1503M-03-F2MC-R-F(1μ″)

Model Name:1.50mm pitch BTB FEMALE SMT R/A TYPE

SCALE:FULL

REVISION:C/0

Drawn: 王程伟 2022.08.10
Checked: 吴丹平
Approved: 林旭芝
DWG NO.CNJST/GCCP-0561